1. Identification

Name of the product: RESTORE-A-DECK WOOD DECK CLEANER

Recommended use: Concentrated wood deck cleaner

Supplier:

RAD OPW LLC 2388 Franklin Rd Bloomfield Hills, MI

EMERGENCY PHONE: 1-800-424-9300 (CHEMTREC)

2. Hazard(s) identification

GHS Classification: Classification of this mixture in accordance with paragraph

(d) of §1910.1200.

Oxidizing Solid – Category 2 Acute Toxicity – Category 4

Eye Damage/Irritation - Category 1

Label elements: Symbol:



Signal word: **DANGER**

Hazard statements: May intensify fire; oxidizer. Harmful if swallowed. Causes serious eye damage. May cause respiratory irritation.

Precautionary statements:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep away from combustible materials. Take any precaution to avoid mixing with combustibles. In case of fire, use water or water spray to extinguish. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapor/spray. Wash thoroughly after handling.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

IF ON SKIN: Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Immediately call a poison center/doctor.

Storage: Store locked up

Disposal: Dispose of contents/container to an approved disposal

facility.

Other Hazards: None known

Other Information: Harmful to the aquatic life.

Keep out of reach of children

3. Composition / Information on ingredients

| CHEMICAL NAME | CAS NUMBER | WEIGHT % |
|--------------------------------|------------|----------|
| Sodium carbonate peroxyhydrate | 15630-89-4 | 70 - 80% |
| Disodium trioxosilicate | 6834-92-0 | < 20% |
| Sodium tripolyphosphate | 7758-29-4 | < 20% |
| Tetraacetylethylenediamine | 10543-57-4 | 10 – 15% |

4. First aid measures

Inhalation:

If adverse effects such as dizziness, nausea or irritation are noted, move person to fresh air. Contact a physician if you feel unwell.

Skin contact:

Wash with soap and water. Get medical attention if irritation persists after washing.

Eye contact:

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician if irritation persists.

Ingestion:

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.

5. Firefighting measures

Suitable extinguishing media: Water or water spray.

Specific hazards in case of fire: May decompose upon heating to produce oxides of carbon.

Special protective equipment and precaution for fire fighters: For fires in enclosed areas, wear self-contained breathing apparatus. Do not inhale combustion gases. Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

6. Accidental release measures

Personal precautions:

Prevent contact with skin, eyes or clothing. Use personal protective equipment as required.

Environmental precautions:

Do not release to the environment or water source.

Methods and materials for containment and cleaning up:

Halt spill at source and contain or dike spill with sand or inert absorbent material. Transfer any liquid to containers for recovery or disposal. Collect used absorbent into drums for disposal in accordance with all applicable local and national regulations.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes; wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including incompatibilities:

Store in a dry location at room temperature. Keep container closed and maintain all original markings and labels. Keep out of reach of children. Incompatible with chlorine bleach.

8. Exposure controls / personal protection

Occupational exposure limits:

| Ingredient(s) | CAS# | ACGIH | OSHA |
|--------------------------------|------------|----------------------|-------------------|
| Sodium carbonate peroxyhydrate | 15630-89-4 | 1 mg/m3 | 2 mg/m3 |
| Disodium trioxosilicate | 6834-92-0 | No data available | 2 mg/m3 |
| Sodium tripolyphosphate | 7758-29-4 | No data available | 2 mg/m3 |
| Tetraacetylethylenediamine | 10543-57-4 | 3 mg/m3 | No data available |

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Respiratory protection:

None required in well-ventilated areas. Any approved organic vapor full-face respirator is advised for poorly ventilated areas.

Eye protection:

Chemical splash goggles.

Skin protection:

Chemical resistant gloves and chemical resistant clothing.

Work hygienic practices: Cleanse skin thoroughly after contact, before breaks and meals and at the end of the work shift.

9. Physical and chemical properties

Physical state: Solid

Color: White **Odor:** Odorless

pH-value: > 10

Freezing Point: Not applicable

Initial boiling point: Not applicable

Flash point: None

Evaporation rate (Water=1): Not applicable Upper flammability limit: No data available Lower flammability limit: No data available

Vapor pressure: No data available

Vapor density (Water Vapor=1): No data available

Specific gravity: No data available

Solubility: Complete in water.

Partition coefficient: No data available

Autoignition temperature: No data available **Decomposition temperature:** No data available

Volatile Organic Compounds (VOC): 0 lbs/gal (EPA method 24)

Viscosity: Not applicable

10. Stability and reactivity

Chemical stability: Unstable on exposure to heat or moisture. Promotes combustion.

Hazardous polymerization: Will not occur.

Conditions to avoid: Avoid raising dust. Keep away from naked flames/heat

Materials to avoid: Combustible materials, oxidizing agents, (strong) acids, (strong)

bases, metals, organic materials, water/moisture, steel

Hazardous decomposition products: Oxides of carbon.

11. Toxicological information

Likely routes of exposure: Eyes, skin, ingestion, inhalation

Symptoms of exposure:

Eye contact: Causes serious eye damage **Skin contact:** Contact causes skin irritation

Inhalation: May cause irritation of respiratory tract

Ingestion: Harmful if swallowed
Immediate, delayed, chronic effects:
Product information: No data available
Target organ effects: Eyes, skin, kidneys

Component acute toxicity information:

| CHEMICAL NAME | ORAL LD50 | DERMAL LD50 | INHALATION LC50 |
|---|----------------------------|--------------------------|--------------------------|
| Sodium carbonate peroxyhydrate 15630-89-4 | 1,034 mg/kg (rat) | >2,000 mg/kg (rabbit) | No data available |
| Disodium trioxosilicate 6834-92-0 | 600 – 1,350 mg/kg (rat) | No data available | No data available |
| Sodium tripolyphosphate 7758-29-4 | 3,120 mg/kg (rat) | >4,640 mg/kg (rabbit) | No data available |
| Tetraacetylethylenediamine 10543-57-4 | > 2,000 mg/kg (rat) | > 2,000 mg/kg (rat) | > 2.08 mg/l, 4h (rat) |

12. Ecological information

Ecotoxicity:

| CHEMICAL NAME | ALGAE/AQUAT IC PLANTS | FISH | MICRO- ORGANISMS | INVERTEBRATES |
|--|---|---|--|---|
| Sodium carbonate peroxyhydrate 15630-89-4 | No data available | LC50: 70.7 mg/l Exposure time: 48 h Species: Pimephales promelas | No data available | LC50: 4.9mg/l Exposure time: 48 h Species: Daphnia pulex |
| Disodium trioxosilicate 6834-92-0 | No data available | No data available | No data available | No data available |
| Tetraacetylethy lenediamine 10543-57-4 | EC50: > 1,000 mg/l Exposure time: 72 h Species: Desmodesmus subspicatus | LC50: > 500 mg/l Exposure time: 96 h Species: Danio rerio | EC50: > 1,000 mg/l Exposure time: 3 h | EC50: > 1,000 mg/l Exposure time: 48 h Species: Daphnia magna |

Persistence and degradability: Harmful to aquatic life. **Bioaccumulation:** No data available but expected not to bioaccumulate based on ingredients.

13. Disposal considerations

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code: D002

Waste from residues / unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

US DOT PROPER SHIPPING NAME: UN3085, OXIDIZING SOLID, CORROSIVE, N.O.S. (SODIUM CARBONATE PEROXYHYDRATE, DISODIUM TRIOXOSILICATE), 5.1 (8), PG III

15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

SARA 313 (TRI reporting)

Not regulated.

California Proposition 65

This product does not contain any Proposition 65 chemicals.

16. Other information

HMIS HAZARD RATING INFORMATION:

HEALTH: 2 FIRE: 0 REACTIVITY: 1 SPECIAL: OX

4=Extreme

3=High

2=Moderate

1=Slight

0=Insignificant

HMIS PROTECTION:

None required under normal conditions of use. If there is an opportunity for splashing:







SDS preparation date: March 26, 2015

SDS revision date: April 25, 2018 Section 1

The information contained herein is accurate to the best of our knowledge. RAD OPW LLC makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances.